



HCS
Air operated hydraulic unit

Model	HCSD-HG2□-□	
Pump quantity	X6308UG x 1 unit	
Valve switching system	Pilot air	
Discharge pressure	MPa	24.5
Driving air pressure	MPa	0.47
Discharge volume (at no load)	L/min	1.3
Oil tank capacity	L	LOW LEVEL : 1.5 / UPPER : 3.5
Set pressure of pressure switch	MPa	14.7 (INC.)
Set pressure of relief valve	MPa	27.9
Air consumption rate	Nm ³ /min	Max. 0.4
Operating temperature	°C	0 ~ 50

• Fluid : water glycol system working oil



HCL
Air operated hydraulic unit

Model	HCLD-HG2□-□	HCLD-HG22□-□
Pump quantity	X6308UG x 1 unit	X6308UG x 2 units
Valve switching system	Air pilot system	
Discharge pressure	MPa	24.5
Driving air pressure	MPa	0.47
Discharge volume (at no load)	L/min	1.3 2.6
Oil tank capacity	L	LOW LEVEL : 1.5 / UPPER : 3.5
Set pressure of pressure switch	MPa	14.7 / 30.8 (at excessively high pressure)
Set pressure of relief valve	MPa	27.9
Air consumption rate	Nm ³ /min	Max. 0.4 Max. 0.8
Operating temperature	°C	0 ~ 50

• Fluid : water glycol system working oil